

Conforms to OSHA HazCom 2012 Standard and WHMIS 2015

# **SAFETY DATA SHEET**

### **1.1 PRODUCT IDENTIFIER**

Product Name: LEVELVOX 505X

Product Code: SH7735

### **1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE**

Product Use: Surface Preparation

### **1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS**

Name/Address:

VOX YAPI KIMYASALLARI SAN VE TIC LTD STI. Haciyusuf Mescit Mah.Hilal Cad.no:100/1 Karatay Konya TURKEY 42030

Telephone Number: + 90 332 342 0869

### Section 2: HAZARD(S) IDENTIFICATION

# 2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR 1910.1200 (OSHA HAZCOM2012)

Skin Irritation Serious Eye Damage Skin Sensitization Specific Target Organ Toxicity—Single Exposure Specific Target Organ Toxicity—Repeated Exposure Carcinogenicity Category 2 Category 1 Category 1B Category 3 Category 1 Category 1A

### 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD: DANGER!

### 2.2b HAZARD STATEMENTS

Causes skin irritation Causes serious eye damage May cause an allergic skin reaction May cause respiratory irritation Causes damage to lungs through prolonged or repeated inhalation of dust May cause cancer through inhalation of dust

2.2c HAZARD PICTOGRAMS



2.2d PRECAUTIONARY STATEMENTS

i.	PREVENTION	Wash hands thoroughly after handling. Do not breathe dust. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection.
ii.	RESPONSE	If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: call a poison center/doctor. If swallowed: Rinse mouth. Do NOT induce vomiting. If exposed or concerned: get medical advice/attention.
iii.	STORAGE	Store in a well-ventilated place. Store locked up. Keep container tightly closed.
iv.	DISPOSAL	Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations.

### 2.3 ADDITIONAL INFORMATION

### 2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED Not Applicable

### 2.3b UNKNOWN ACUTE TOXICITY

2.3% of the mixture consists of ingredient(s) of unknown acute toxicity.

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

### **3.1 MIXTURES**

Chemical Name	CAS Number	Weight %
Calcite (Ca(CO3))	13397-26-7	40 – 70%*
Portland Cement	65997-15-1	15 – 35%*
Calcium Carbonate	1317-65-3	5 – 15%*
Polymeric compounds	9004-65-3	1 – 5%*

\*Means that the component will fall into one the ranges specified due to batch-to-batch variability.

### Section 4: FIRST-AID MEASURES

### 4.1 DESCRIPTION OF THE FIRST-AID MEASURES

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
Skin Contact:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
Inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
Ingestion:	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

#### 4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Skin Contact:	Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact.
Inhalation:	May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.
Ingestion:	May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

### 4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Note to Physicians:	Symptoms may not appear immediately.
Specific Treatments:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### Section 5: FIRE-FIGHTING MEASURES

#### 5.1 FLAMMABILITY

Flammability: Not Flammable/Not Combustible by WHMIS/OSHA HAZCOM2012 Criteria

### **5.2 EXTINGUISHING MEDIA**

- **5.2a. Suitable Extinguishing Media:** Treat for surrounding material
- 5.2b. Unsuitable Extinguishing Media: Not Available

### 5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

#### 5.3a. Explosion Data

- i. Sensitivity to Mechanical Impact: Not Available
- ii. Sensitivity to Static Discharge: Not Available

### 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full bunker gear) and respiratory protection (SCBA).

### Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment:	Recover all usable material. Pick up large pieces, and then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for Cleaning-Up:	Vacuum or sweep material and place in a disposal container. Dispose of unwanted material properly in accordance with all local, regional, national and international regulations.

### Section 7: HANDLING AND STORAGE

### 7.1 PRECAUTIONS FOR SAFE HANDLING

Handling:	Use in well-ventilated areas. Wear impervious gloves and eye protection. Do not mix with other chemical products, except as indicated by the manufacturers. Do not get in eyes. Do not get on skin or clothing. Do not breathe dust. Do not take internally.
General Hygiene Advice:	Use good industrial hygiene practices and wear recommended personal protection. Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage:

Keep out of the reach of children. Store locked up. Keep container tightly closed. Store at room temperature and keep containers closed when not in use. Keep dry until use.

### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **8.1 EXPOSURE CONTROLS**

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

#### 8.2 INDIVIDUAL PROTECTION MEASURES

#### 8.2a. Personal Protective Equipment:

- i. **Eye/Face Protection:** Wear approved eye/face protection [properlyfitted dust- or splash-proof chemical safety goggles/face (face shield)]
- ii. Skin Protection:
  - 1. Hand Protection: Wear impervious gloves, such as nitrile.
  - 2. Body Protection: Wear suitable protective clothing
- iii. Respiratory Protection: A NIOSH approved respirator or filtering face piece, such as N95, is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.

### Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Cement-Based Primer
Odor:	Characteristic
Odor Threshold:	Not Available
pH:	10.0 – 12.5 when wet
Melting point/Freezing point:	Not Available
Initial boiling point and boiling range:	Not Available
Flash point:	>212°F(>100°C)
Evaporation rate (Water=1):	Not Available
Flammability:	Not Flammable/Not Combustible
Upper Flammability/Explosive Limit:	Not Available
Lower Flammability/Explosive Limit:	Not Available
Vapor Pressure	Not Available
Vapor Density:	Not Available
Relative Density:	2.0 – 3.0 g/mL
Solubility in Water:	Slightly Soluble
Partition coefficient: n-octanol/water:	Not Available
Auto-ignition temperature:	Not Available
Decomposition Temperature:	Not Available
Viscosity (cps):	Not Available
VOC Content:	0 g/L

### Section 10: STABILITY AND REACTIVITY

#### 10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

#### **10.2. CHEMICAL STABILITY**

Stable under normal storage conditions. Keep dry in storage.

### **10.3. POSSIBILITY OF HAZARDOUS REACTION**

No dangerous reaction known under conditions of normal use.

### **10.4. CONDITIONS TO AVOID**

Heat. Incompatible materials.

### **10.5. INCOMPATIBLE MATERIALS**

Strong acids. Strong Oxidizers.

#### **10.6. HAZARDOUS DECOMPOSITION PRODUCTS**

Upon decomposition, this product may yield oxides of carbon and hydrogen sulfide.

### Section 11: TOXICOLOGICAL INFORMATION

### 11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

#### 11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

- **Eye Contact:** Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- **Skin Contact:** Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact.
  - **Inhalation:** May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.
  - **Ingestion:** May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

### 11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

SHORT-TERM		
Skin Corrosion/Irritation:	Causes skin irritation	
Serious Eye Damage/Irritation:	Causes severe eye damage	
Respiratory Sensitization:	Not Classified	
Skin Sensitization:	May cause an allergic skin reaction	
STOT-Single Exposure:	May cause respiratory irritation	
Aspiration Hazard:	Not Classified	
LONG-TERM		
Carcinogenicity:	May cause cancer through inhalation of dust	
Germ Cell Mutagenicity:	Not Classified	
Reproductive Toxicity:	Not Classified	
STOT-Repeated Exposure:	Causes damage to lungs through prolonged or repeated inhalation of dust	
Synergistic/Antagonistic Effects:	Not Classified	

### Section 12: DISPOSAL CONSIDERATIONS

### 13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

#### 13.2. OTHER DISPOSAL CONSIDERATIONS Not Available

### Section 14: TRANSPORT INFORMATION

DOT (U.S.)	TDG (CANADA)	ΙΑΤΑ
UN NUMBER:	UN NUMBER:	UN NUMBER:
Not Regulated	Not Regulated	Not Regulated
UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:
Not Regulated	Not Regulated	Not Regulated
TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):
Not Regulated	Not Regulated	Not Regulated
PACKING GROUP (if applicable):	PACKING GROUP (if applicable):	PACKING GROUP (if applicable):
Not Regulated	Not Regulated	Not Regulated

SUMMARY: Product is NOT regulated under DOT/TDG and other transportation regulations.

### 14.1. ENVIRONMENTAL HAZARDS Not Available

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE Not Available

#### 14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

### Section 15: REGULATORY INFORMATION

# 15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

**Canada:** This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

**US:** SDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200) HazCom 2012

### **15.2. US FEDERAL INFORMATION:**

Chemical Name	CAS Number	Weight %
Calcite (Ca(CO3))	13397-26-7	40 – 70%*
Portland Cement	65997-15-1	15 – 35%*
Calcium Carbonate	1317-65-3	5 – 15%*
Polymeric compounds	9004-65-3	1 – 5%*


### 15.3. US STATE RIGHT TO KNOW LAWS:

California Proposition 65:	WARNING: This product can expose you to chemicals including Crystalline Silica which is known to the State of California to cause cancer and Hexavalent Chromium Compounds which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Other U.S. States "Right to Know" Lists:	
New Jersey:	Calcite (Ca(CO3)): CAS#13397-26-7 Calcium Carbonate: CAS#1317-65-3 Portland Cement: CAS#65997-15-1 Gypsum: CAS#13397-24-5 Polymeric compounds: CAS#9004-65-3
Pennsylvania:	Calcite (Ca(CO3)): CAS#13397-26-7 Calcium Carbonate: CAS#1317-65-3 Portland Cement: CAS#65997-15-1 Gypsum: CAS#13397-24-5 Polymeric compounds: CAS#9004-65-3
Massachusetts:	Calcite (Ca(CO3)): CAS#13397-26-7 Calcium Carbonate: CAS#1317-65-3 Portland Cement: CAS#65997-15-1 Gypsum: CAS#13397-24-5 Polymeric compounds: CAS#9004-65-3
Minnesota:	Silica, Quartz: CAS#14808-60-7 Calcium Carbonate: CAS#1317-65-63 Calcium Aluminate Cement: CAS#65997-16-2 Portland Cement: CAS#65997-15-1 Gypsum: CAS#13397-24-5
Florida:	Not Available
Michigan:	Not Available

Conforms to OSHA HazCom 2012 Standard and WHMIS 2015

# SAFETY DATA SHEET

### 15.4. NFPA AND HMIS RATINGS:



Conforms to OSHA HazCom 2012 Standard and WHMIS 2015

# SAFETY DATA SHEET

#### 15.5. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65	California Proposition 65
OSHA (O)	Occupational Safety and Health Administration
ACGIH (G)	American Conference of Governmental Industrial Hygienists
	A1 – Confirmed human carcinogen
	A2 – Suspected human carcinogen
	A3 – Animal carcinogen
	<ul> <li>A4 – Not classifiable as a human carcinogen</li> </ul>
	A5 – Not suspected a human carcinogen
IARC (I)	International Agency for Research on Cancer
	<ul> <li>1 – The agent (mixture) is carcinogenic to humans</li> </ul>
	<ul> <li>2A – The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.</li> <li>2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.</li> <li>3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.</li> <li>4 – The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.</li> </ul>
NTP (N)	National Toxicology Program
	<ul> <li>1 – Known to be carcinogens</li> </ul>
	2 – Reasonably anticipated to be carcinogens

### **Section 16: OTHER INFORMATION**

**Date of Preparation:** 

June 18, 2018

Version:

1.1

**Disclaimer:** The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by:

### VOX YAPI KIMYASALLARI SAN VE TIC LTD STI.

Phone: +90 (332) 342 08-69 www.voxchem.com info@voxchem.com

# **End of Safety Data Sheet**